

Parts News

Americas

Boom Greasing System for Hyd Cranes

A special grease gun vaporizes boom grease, using a compressed air pump that is mounted onto a 25-liter (6.5 Gallons) drum of grease.

- ➔ Ideal for use on any telescopic boom!
- ➔ Prolongs boom wear pad life!
- ➔ Easy and cost effective operation!
- ➔ Rapid application – saves hours over traditional greasing methods!
- ➔ Efficient application – little or no waste!
- ➔ No mess to cleanup – friendly to the environment!



SPRAY GUN



Lightweight, sturdy and very easy to use! The spray gun automatically ensures that the proper mixture of LS2 grease is combined with air. The 10 meter (32 feet) armored hose allows freedom of movement in the workspace and stores conveniently.

PNEUMATIC PUMP



The pump is easily connected to an external compressed air supply. The whole unit is mounted on a sturdy cart - easy to move - easy to store.

Order P/N 03325445 for the complete unit with the spray gun, reinforced high pressure hose, flexible sheathing and connecting accessories.

Order P/N L0137345825KG for 25-liter (6.5 Gallons) drum of high density LS2 grease. (*"LS" is a high-quality lithium-based class of grease suitable for operating temperatures between -30 and 120°C (-22F to 248 F). Resistant to water and high-pressure steam. Also contains oxidation and corrosion inhibitors.*

Think GREEN - Rapid! Clean! Efficient!

Contact your nearest Manitowoc Crane Care dealer by clicking on:

<http://www.manitowoccranes.com/DealerLocator/locator.asp>

or email cranecare.marketing@manitowoc.com.